



ConTec CS-640

SEALER

DESCRIPTION

ConTec CS-640 sealer is a water-based emulsion of organomodified siloxanes/silanes. It is designed to give concrete tough, water-resistant properties. It excels on concrete roof tile. ConTec CS-640 is proven effective on porous concrete masonry surfaces. Properly applied CS-640 aids in the prevention of moss and algae growth.

APPLICATION

Spray systems should be airless type. There is no need to over apply. Only one coat is required. Apply only when substrate and ambient temperatures are above 64 degrees F. High volume users may consider buying CS-640 concentrate. Consult your ICT representative about our automated inline mixing units.

PACKAGING

ConTec CS-640 is available in bulk quantities or packaged in 55 gallon (208 L) drums weighing 480 lbs (218 kg) and 265 gallon (1003 L) totes weighing 2360 lbs (1070 kg).

TYPICAL PROPERTIES

Specific Gravity at 77F.....	1.00 - 1.02
Viscosity at 77F, cps	100 max
Weight per gallon	8.35 - 8.4
% Volatile matter (NVM(1))	~ 50

FEATURES / BENEFITS

- Deep penetrating.
- Good water repellency.
- Fast Drying - Reduces Blocking.
- Improves durability and chemical resistance.
- Reduces efflorescence on concrete products.
- Self cleaning effect.
- Excellent price/performance ratio.
- Can be applied on dry or green concrete.
- Tolerates heat accelerated drying.

HANDLING / STORAGE

ConTec CS-640 can be stored over a wide range of temperatures but should not be allowed to freeze. Should ConTec CS-640 freeze, it will not thaw to a usable product. Provide adequate ventilation with use.

APPLICATION RATES

Application rates can vary, depending on surface, from 100 to 500 square feet per gallon. Typical roof tile application rates average 9 grams per square foot. Optimum coverage rates vary with geographic area and the texture and composition of the surface being sealed. Always consult your ICT technical representative for recommendations for your application.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

Innovative Concrete Technology, LLC

bestadmix.com

Two Wall Street – Oxford, NJ 07863 • Ph. 908-453-2737 • Fax 908-453-3634